

# PD1350 REMOVER for SOLVENT BASED SEALERS

Removes solvent based acrylic sealers.

## PRODUCT CODE, SIZE & PACKAGING

Ready to use formula

Code: PD1350-01 946ml – 6 or 12 per case

Code: PD1350-04 4 liters - 4 per case

Code: PD1350-20 20 liters – 1 pail



## DIRECTIONS

## PREVENTION MEASURES

### PERSONAL SAFETY

Wearing of gloves, safety glasses and appropriate clothing to prevent skin contact when using the product is always recommended.

Please follow safety guidelines outlined in the "CAUTION" section indicated on the bottle (see hereunder).

### NEIGHBORING AREA PROTECTION

Always protect the neighboring working area against unexpected contact with the product to avoid irreversible damage or alterations that could only be restored by its replacement.

### PREREQUISITE CONDITIONS

**Surface temperature should be between 15 and 30°C (59 and 86°F).**

Ideal temperature for best results.

**Test first on a small and adequate surface, to assess results.**

**- First time user, without preliminary testing.**

Never use the product for the first time on a large area without preliminary testing.

Usage of the product on an alkaline sensitive material could alter irreversibly the covering material that would only be restored by its replacement.

**- Using the product on a new surface or on an unknown surface, without preliminary testing.**

Even if you have used the product in the past, because covering manufacturers do modify occasionally the composition of their products, there could be, without your knowledge, presence of an incompatible substance that could be irreversibly damaged or altered or give unexpected end results that would only be restored by its replacement.

More so, even if the product is lightly alkaline, it could damage the finish or the protection of certain materials. Some acrylics (bathtubs, showers, sinks) are sensitive to alkaline cleaning products combined with the scrubbing action of nylon scuff pads.

## RECOMMENDED SURFACES:

- Safe for
- Ceramic and porcelain
- Slate
- Granite
- Marble & calcareous stones
- Concrete
- Counters, floors and walls
- Residential, commercial and institutional
- Interior and exterior applications

## CHARACTERISTICS:

- Viscous formula and slow evaporation for a long term action
- Low odor
- Safe on metals

## PERFORMANCE:

- Meets the efficiency test of Solvent Based Sealer Remover ASTM D1792-06

## RESTRICTIONS:

- Can damage MDF planks and boards
- May damage sealers and floor finishes
- May damage pre-mixed grout

<p><b>METHOD OF APPLICATION</b></p> <p><b><u>Sealer removal:</u></b>          Spread a generous coat of remover evenly all over the surface.          Let the remover work 30 to 60 minutes, while scrubbing the surface every 10 minutes with black nylon scuff pads or a hard bristle brush.          Time required to soften coats of sealer will vary with the chemical composition and the thickness of the coats as well as for the room temperature and texture of the surface.          When the sealer is softened, mix in a 25% concentrated solution of HEAVY DUTY CLEANER PD1010 and scrub to free surface from all residues.          Remove with preferably a wet vacuum and rinse thoroughly with clear water.          Repeat if necessary.          Allow to dry 24 hours before applying a sealer.</p> <p><b>APPLICATION PROBLEMS</b></p> <p><b><u>Sealer residues still apparent after removal procedure:</u></b></p> <p>The sealer removal procedure will vary with the chemical composition of the sealer. Some old solvent based sealers were formulated with resins that are no longer available and which were extremely resistant to different solvents.</p> <p><b><u>Main causes:</u></b>          -Solvent resistant sealer.          -Not have given enough working time to the remover</p> <p><b><u>Corrective measures:</u></b>          -Wash the surface with a 25% concentrated solution of HEAVY DUTY CLEANER PD1010 and scrub the area with black nylon scuff pads. Rinse thoroughly with water and remove solution with a wet vacuum.          or          -Repeat the procedure, adjusting the quantity of remover applied on the surface with the appropriate working time and/or making sure the rinsing procedure is performed thoroughly, leaving no traces of sealer.</p> <p><b><u>Sticky surface after removal procedure:</u></b></p> <p>This problem usually occurs when residues of remover and sealer are still present on the surface.</p> <p><b><u>Main causes:</u></b>          -Surface was not properly cleaned and/or rinsed.</p> <p><b><u>Corrective measures:</u></b>          Rinse with 25% concentrated solution of HEAVY DUTY CLEANER PD1010 and scrub to remove all residues.          Pick-up with preferably a wet vacuum and rinse thoroughly with clear water.          If residues are still apparent, repeat removal procedure.</p>	<p><b><u>LIMITATIONS:</u></b>          -Efficiency varies with the chemical composition of the sealers.</p> <p><b><u>ENVIRONMENTAL DATA:</u></b>          -VOC: 0          -Biodegradable. In conformity with OCDE 301 E rule          -Meets ecologic environmental standards for Removers, Paints &amp; Varnishes</p> <p><b><u>COVERAGE</u></b>          946ml approx 10m<sup>2</sup> (100ft<sup>2</sup>)          4liters approx 40m<sup>2</sup> (400ft<sup>2</sup>)</p> <p>Varies with the chemical composition and the thickness of the coats of sealer as well as the surface condition.</p>
<p><b>HANDLING &amp; STORAGE</b></p> <p>Avoid freezing.          Store in original container, well closed, in a dry area at room temperature.          Do not waist excess sealer in sewers.          Send them to an appropriate recycling center.          Shelf life: 2 years in a tight closed container at a temperature between 10 and 30°C (50 and 86°F).</p>	<p>CAUTION</p> <p>MAY IRRITATE EYES          MAY IRRITATE SKIN          Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Keep out of reach of children.</p> <p><b>FIRST AID TREATMENT</b>          Contains glycols.          If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes with eye lids open. If on skin, rinse well with water.</p>

**TECHNICAL SUPPORT**

Communicate at [info@saniten.ca](mailto:info@saniten.ca) or call 1-866-517-7662.

N.B. All information here above is accurate. But having no control over the conditions of utilization of the product, we cannot assume any responsibility, legal or other, in regards of the results and/or any prejudice derived from.

Revised January 2017