

PD1425 BLACK GLUE & CARPET GLUE REMOVER

Removes black glue residues on VCT tiles and concrete as well as carpet glues and acrylic tile adhesives.

PRODUCT CODE, SIZE & PACKAGING

Ready to use formula

Code: PD1425-01 946ml – 6 or 12 per case

Code: PD1425-04 4 liters - 4 per case

Code: PD1425-20 20 liters – 1 pail



DIRECTIONS

PREVENTION MEASURES

PERSONAL SAFETY

Wearing of gloves, safety glasses and appropriate clothing to prevent skin contact when using the product is always recommended.

Please follow safety guidelines outlined in the "CAUTION" section indicated on the bottle (see hereunder).

NEIGHBORING AREA PROTECTION

Always protect the neighboring working area against unexpected contact with the product to avoid irreversible damage or alterations that could only be restored by its replacement.

PREREQUISITE CONDITIONS

Surface temperature should be between 15 and 30°C (59 and 86°F).

Ideal temperature for best results.

Test first on a small and adequate surface, to assess results.

- First time user, without preliminary testing.

Never use the product for the first time on a large area without preliminary testing.

Usage of the product on an alkaline sensitive material could alter irreversibly the covering material that would only be restored by its replacement.

- Using the product on a new surface or on an unknown surface, without preliminary testing.

Even if you have used the product in the past, because covering manufacturers do modify occasionally the composition of their products, there could be, without your knowledge, presence of an incompatible substance that could be irreversibly damaged or altered or give unexpected end results that would only be restored by its replacement.

More so, even if the product is lightly alkaline, it could damage the finish or the protection of certain materials. Some acrylics (bathtubs, showers, sinks) are sensitive to alkaline cleaning products combined with the scrubbing action of nylon scuff pads.

Finally, since 2016 we note that some polished Quartz products, Quartzite surfaces and

RECOMMENDED SURFACES:

- Safe for
- Ceramic and porcelain
- VCT Vinyl Composite Tiles
- Concrete
- Floors
- Residential, commercial and institutional
- Interior and exterior applications

CHARACTERISTICS:

- Viscous formula and slow evaporation for a long term action
- Low odor
- Safe on metals

PERFORMANCE:

- Meets efficiency test for Carpet and Black Glue Remover ASTM D4488-95-A5

RESTRICTIONS:

- Can damage MDF planks and boards
- May damage sealers and floor finishes
- May damage pre-mixed grout

flamed granites are very sensitive to alkaline products. Application of a wax or an acrylic finish by the manufacturers seems to be at the origin of the problem.

METHOD OF APPLICATION

Old glue residue removal:

Spread a generous coat of remover evenly all over the surface.
Let the remover work 15 to 30 minutes, while scrubbing the surface every 10 minutes with black nylon scuff pads or a hard bristle brush.
Time required to soften material will vary with the chemical composition and the thickness of the glue residues as well as for the surface temperature and texture.
When the glue is softened by the remover, mix in a 25% concentrated solution of HEAVY DUTY CLEANER PD1010 and scrub to remove all glue residues.
Remove with preferably a wet vacuum and rinse thoroughly with clear water.
Repeat if necessary.
Allow to dry 24 hours before applying a sealer, paint or another adhesive.

Optional: For concrete surfaces, you can wash the floor with a solution of GROUT & TILE CLEANER N305 to open the porosity of the cement surface before the application of a sealer, paint, glue or an adhesive.

Black-out and acrylic glue excess removal on VCT tiles:

Spread a coat of remover on the joints.
Let the remover work 15 minutes or until the glue residues are soften
Using a blade or a spatula, remove the excess glue on the tiles.
Time required to soften material will vary with the chemical composition and the thickness of the glue to be removed as well as for the temperature and texture of the surface.
After residues are removed, wash the surface with a 25% concentrated solution of HEAVY DUTY CLEANER PD1010 and scrub to remove remaining glue residues.
Remove with preferably a wet vacuum and rinse thoroughly with clear water.
Repeat if necessary.
Allow to dry 24 hours before applying a sealer or a floor finish.

APPLICATION PROBLEMS

Glue residues still apparent after removal procedure:

The glue removal procedure results will vary with the chemical composition of the glue. Some old glues were formulated with resins that are no longer available and which were extremely resistant to different solvents.

Main causes:

- Solvent resistant glue.
- Not have given enough working time to the remover

Corrective measures:

-Repeat the removal procedure, adjusting the quantity of remover applied on the surface with the appropriate working time and/or making sure the rinsing procedure is performed thoroughly, leaving no traces of residues to the touch.
If afterwards, it seems impossible to free the surface from the glue residues, you will have no choice but to sandblast the surface

Sticky surface after removal procedure:

This problem usually occurs when residues of remover and glue are still present on the surface.

Main causes:

- Surface was not properly cleaned and/or rinsed.

Corrective measures:

Rinse with 25% concentrated solution of HEAVY DUTY CLEANER PD1010 and scrub to remove all residues.
Pick-up with preferably a wet vacuum and rinse thoroughly with clear water.
Repeat if necessary.

LIMITATIONS:

-Efficiency varies with the chemical composition of the glue residues

ENVIRONMENTAL DATA:

-VOC: 0
-Biodegradable. In conformity with OCDE 301 E rule
-Meets Ecologic Environmental standards for Removers, Paints & Varnishes

COVERAGE

946ml approx 10m² (100ft²)
4liters approx 40m² (400ft²)

Varies with the chemical composition and the thickness of the residues as well as the surface condition.

<p>HANDLING & STORAGE</p> <p>Avoid freezing. Store in original container, well closed, in a dry area at room temperature. Do not waist excess sealer in sewers. Send them to an appropriate recycling center. Shelf life: 2 years in a tight closed container at a temperature between 10 and 30°C (50 and 86°F).</p>	<p>CAUTION</p> <p>MAY IRRITATE EYES MAY IRRITATE SKIN Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Keep out of reach of children.</p> <p>FIRST AID TREATMENT Contains glycols. If swallowed, call a Poison Control Centre or doctor immediately. Do not Induce vomiting. If in eyes, rinse with water for 20 minutes with eye lids open. If on skin, rinse well with water.</p>
<p>TECHNICAL SUPPORT</p> <p>Communicate at info@saniten.ca or call 1-866-517-7662.</p> <p>N.B. All information here above is accurate. But having no control over the conditions of utilization of the product, we cannot assume any responsibility, legal or other, in regards of the results and/or any prejudice derived from.</p>	<p>Revised January 2017</p>