

DIVISION DE:

Adhésifs



[www.saniten.ca](http://www.saniten.ca)

## PD1700 GRAFFITI REMOVER

Removes graffiti paint on brick, concrete, wood, vinyl, aluminum and galvanized steel

### PRODUCT CODE, SIZE & PACKAGING

Ready to use formula

Code: PD1700-07 700ml with spray gun – 12 per case

Code: PD1700-01 946ml – 6 or 12 per case

Code: PD1700-20 4 liters - 4 per case



### DIRECTIONS

### PREVENTION MEASURES

#### PERSONAL SAFETY

Wearing of gloves, safety glasses and appropriate clothing to prevent skin contact when using the product is always recommended.

Please follow safety guidelines outlined in the "CAUTION" section indicated on the bottle (see hereunder).

#### NEIGHBORING AREA PROTECTION

Always protect the neighboring working area against unexpected contact with the product to avoid irreversible damage or alterations that could only be restored by its replacement.

#### PREREQUISITE CONDITIONS

**Surface temperature should be between 15 and 30°C (59 and 86°F).**

Ideal temperature for best results.

**Test first on a small and adequate surface, to assess results.**

#### **- First time user, without preliminary testing.**

Never use the product for the first time on a large area without preliminary testing.

Usage of the product on an alkaline sensitive material could alter irreversibly the covering material that would only be restored by its replacement.

#### **- Using the product on a new surface or on an unknown surface, without preliminary testing.**

Even if you have used the product in the past, because covering manufacturers do modify occasionally the composition of their products, there could be, without your knowledge, presence of an incompatible substance that could be irreversibly damaged or altered or give unexpected end results that would only be restored by its replacement.

More so, even if the product is designed to remove safely graffiti, colors and finish of certain materials could be altered irreversibly and would only be restored by their replacement.

### **RECOMMENDED SURFACES:**

- Brick
- Concrete
- Vinyl, galvanized steel and aluminum sidings
- Walls
- Residential, commercial and institutional
- Interior and exterior applications

### **CHARACTERISTICS:**

- Viscous formula for a long lasting action and vertical application
- Slow evaporation for a long term action
- Low odor
- Safe for metals

### **PERFORMANCE:**

- Meets Solvent Based Sealer Removal Test ASTM D6189-97

### **ENVIRONMENTAL DATA:**

- VOC: 0
- Biodegradable. In conformity with OCDE 301 E rule
- Meets Ecologic Environmental standards for Removers, Paints & Varnishes

### **LIMITATIONS:**

- This product will damage non surface-baked paints.

<p><b>METHOD OF APPLICATION</b></p> <p>Use straight from the bottle, without dilution.  Apply directly on the graffiti, let work 2 to 3 minutes and scrub with a white nylon scuff pad, a nylon brush or a rag.  The required time of action will vary with the chemical composition and the thickness of the paint as well as with the surface porosity and the temperature.  Rinse thoroughly with clear water.  Removal of graffiti and rinsing with a pressure washing machine is recommended.  Repeat if necessary.  Allow to dry 24 hours before applying paint or a sealer.</p> <p><b>APPLICATION PROBLEMS</b></p> <p><b><u>Graffiti halo visible after cleaning procedure:</u></b> This happens mostly when the surface is porous like concrete or textured like brick.</p> <p><u>Main causes:</u>  - This problem occurs because the paint is in the surface pores too small to be reached and scrubbed off.</p> <p><u>Corrective measures:</u>  -Remover can be left on the surface longer to allow better graffiti dilution. Also some active ingredients in the remover will be absorbed during the cleaning process and will continue to work even after rinsing. You may see the graffiti halo disappear with time.</p> <p><b><u>Surface where graffiti was removed became matte:</u></b> This happens mostly because of the joint effect of the contact with the remover and the scrubbing action on the surface material.</p> <p><u>Main causes:</u>  - This problem occurs because the remover doesn't only work on the graffiti but also on the painted surface where the graffiti was located.</p> <p><u>Corrective measures:</u>  -There are no remedies but to repaint or change the material. This is why it is extremely important to make a test on as small area to make sure the procedure won't end up damaging the material.</p>	<p><b><u>COVERAGE</u></b></p> <p>700ml – approx 100pi<sup>2</sup>  946ml – approx 150pi<sup>2</sup>  4 litres – approx 600pi<sup>2</sup></p> <p>Varies with the chemical composition and the thickness of the paint as well as the surface porosity.</p>
<p><b>HANDLING &amp; STORAGE</b></p> <p>Avoid freezing.  Store in original container, well closed, in a dry area at room temperature.  Do not waist excess sealer in sewers.  Send them to an appropriate recycling center.  Shelf life: 2 years in a tight closed container at a temperature between 10 and 30°C (50 and 86°F).</p>	<p>CAUTION</p> <p>MAY IRRITATE EYES  MAY IRRITATE SKIN  Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Keep out of reach of children.</p> <p><b>FIRST AID TREATMENT</b>  Contains glycols.  If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes with eye lids open. If on skin, rinse well with water.</p>
<p><b>TECHNICAL SUPPORT</b></p> <p>Communicate at <a href="mailto:info@saniten.ca">info@saniten.ca</a> or call 1-866-517-7662.</p> <p>N.B. All information here above is accurate. But having no control over the conditions of utilization of the product, we cannot assume any responsibility, legal or other, in regards of the results and/or any prejudice derived from.</p>	<p>Revised January 2017</p>