



DIVISION DE: Adhésifs
PROMA
Adhesives Inc.

www.saniten.ca

PR90 TILE PROTECTOR for GROUTING

Tile protector acting as a grout release, to prevent all types of grouts to stick on the surface of tiles and ease grout residue clean-up.

PRODUCT CODE, SIZE & PACKAGING

Ready to use formula

Code: PR90-01 946ml – 6 or 12 per case

Code: PR90-04 4 liters - 4 per case

Code: PR90-20 20 liters – 1 pail

DIRECTIONS

PREVENTION MEASURES

PERSONAL SAFETY

Wearing of gloves, safety glasses and appropriate clothing to prevent skin contact when using the product is always recommended.

Please follow safety guidelines outlined in the “CAUTION” section indicated on the bottle (see hereunder).

NEIGHBORING AREA PROTECTION

Always protect the neighboring working area against unexpected contact with the product to avoid irreversible damage or alterations that could only be restored by its replacement

PREREQUISITE CONDITIONS

Surface temperature should be between 15 and 30°C (59 and 86°F).

Ideal temperature for best results.

Test first on a small and adequate surface, to assess results.

- First time user, without preliminary testing.

Never use the product for the first time on a large area without preliminary testing.

Usage of the product on an alkaline sensitive material could alter irreversibly the covering material that would only be restored by its replacement.

- Using the product on a new surface or on an unknown surface, without preliminary testing.

Even if you have used the product in the past, because covering manufacturers do modify occasionally the composition of their products, there could be, without your knowledge, presence of an incompatible substance that could be irreversibly damaged or altered or give unexpected end results that would only be restored by its replacement.

RECOMMENDED SURFACES:

- Ceramic and porcelain
- Luxury Vinyl Tiles (LVT)
- Natural stones
- Quartz
- Acrylic baths and showers
- All types of grout

CHARACTERISTICS

- Fast drying
- Water soluble
- Odorless

ENVIRONMENTAL DATA:

- VOC: 0
- Biodegradable. In conformity with OCDE 301E rule

LIMITATIONS:

- This product is not designed to replace tile manufacturer's recommendation to use a sealer on certain tiles for protection against grout staining.

To that effect sealers such as: PENETRATING SEALER PS670 and PENETRATING SEALER MICROTECH PS400 are recommended.

ACCESSORIES:

- TP450 White nylon scuff pad

<p>METHOD OF APPLICATION</p> <p>Use straight from the bottle, without dilution. Pour on a white scuff pad and spread a thin coat on the surface of the tiles. Never pour the GROUT PROTECTOR directly on the surface of the tiles before spreading it to avoid filling the joints with the product. For large areas, you can use a paint roller with short nap and a paint pan. For heavy porous or textured surfaces a thick coat or application of a 2nd coat is recommended. Wait approximately 30 to 40 minutes to allow the TILE PROTECTOR for GROUTING PR90 to dry completely before grouting the surface as usual. Follow the grout manufacture's recommendations. The product being 100% water soluble, it will be removed during the clean-up process with water and a sponge.</p> <p>APPLICATION PROBLEMS</p> <p><u>Apparent grout residues on the tiles after clean-up:</u> This is not a frequent but can happen with highly textured or porous surfaces.</p> <p><u>Main causes:</u> - This problem occurs when the quantity of TILE PROTECTOR for GROUTING PR90 applied was insufficient to fill all surface lumps and pin-holes.</p> <p><u>Corrective measures:</u> Because we cannot go back and start over the work adding more TILE PROTECTOR for GROUTING PR90 on the surface of the tiles, grout residues will have to be removed with the appropriate grout residue remover.</p> <p>Cement grout (sanded or un-sanded) CEMENT GROUT RESIDUE REMOVER PR2000 or in the presence of marble and calcareous stones CEMENT GROUT RESIDUE REMOVER – MARBLE & CALCAREOUS STONES PD1500</p> <p>Cement grout mixed with an additive CEMENT GROUT RESIDUE REMOVER – MARBLE & CALCAREOUS STONES PD1500</p> <p>Epoxy grout EPOXY REMOVER PD1600 or EPOXY GROUT RESIDUE REMOVER PD1900</p> <p>Pre-mixed grout (acrylic or urethane) PRE-MIXED GROUT RESIDUE REMOVER PD1050</p>	<p><u>COVERAGE</u> 15m² / 150pi² : 946ml 60m² / 600pi² : 4 liters</p> <p>Varies with the method of application and the surface condition.</p>
<p>HANDLING & STORAGE</p> <p>Avoid freezing. Store in original container, well closed, in a dry area at room temperature. Do not waist excess sealer in sewers. Send them to an appropriate recycling center. Shelf life: 2 years in a tight closed container at a temperature between 10 and 30°C (50 and 86°F).</p>	<p>CAUTION</p> <p>MAY IRRITATE EYES Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children.</p> <p>FIRST AID TREATMENT Contains surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes with eye lids open. If on skin, rinse well with water.</p>
<p>TECHNICAL SUPPORT</p> <p>Communicate at info@saniten.ca or call 1-866-517-7662.</p> <p>N.B. All information here above is accurate. But having no control over the conditions of utilization of the product, we cannot assume any responsibility, legal or other, in regards of the results and/or any prejudice derived from.</p>	<p>Revised January 2017</p>