

PAVING STONE SEALER

HIGH GLOSS

www.saniten.ca

February 15, 2014

Solvent based acrylic sealer formulated to protect and embellish paving stone leaving a high gloss finish

DIRECTIONS

SURFACE PREPARATION

New installation: Wash the surface with SANITEN Industrial Cleaner Acid Cleaner PR2000.

Existing installation: Deep clean the surface with SANITEN Heavy Duty Cleaner PD1010.

APPLICATION

Before applying the sealer, make sure that the temperature will remain dry and above 10°C for 2 consecutive days.

With a paint brush or a paint roller, apply a thin coat of sealer. Avoid air bubbles and streaks while applying the sealer. Let dry completely (4 to 6 hours) before applying another coat. We recommend the application of 2 coats. Normal circulation after 24 hours. Curing time: 28 days.

CAUTION & LIMITATIONS

MAY IRRITATE EYES. MAY IRRITATE SKIN. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Keep out of reach of children. Keep away from flames or sparks.

FIRST AID TREATMENT

Contains mineral spirit. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting as product could be aspirated into lungs. If in eyes, rinse with water for 20 minutes with eye lids open. If on skin, rinse well with water. If on clothes, remove clothes.

Test first the product on a small and adequate area.

Protect the neighboring area against unexpected contact with the product. Surface temperature must be between 15 and 25°C.

Keep away from heat, sparks and flames. Flammable product. Flash point >43°C. Do not apply on grouted surfaces.

PACKAGING

3,78 litres - 4 per case

18,9 litres - pail

COVERAGE

3,78 litres cover approximately 70m² (700ft²).

HANDLING & STORAGE

Avoid from freezing.

Store in original container, well closed in a dry area at room temperature.

Shelf life: 2 years

Do not put excess sealer in the garbage.

Dispose in an appropriate waste site.

TECHNICAL SUPPORT

Refer to the web site www.saniten.ca or call 1-877-726-5836.



Product code: PS1845

RECOMMENDED SURFACES:

- Paving stone
- Non grouted textured natural stones
- Residential and commercial applications
- Exterior use

CHARACTERISTICS:

- Enhances stone colors
- Gloss rating: >70
- Provides water and oil repellent protection
- Solvent: mineral spirit
- Aromatic odor
- Good leveling
- Dries quickly

REMOVER:

- Solvent Based Sealer Remover PD1350

N.B. All information here above is accurate. But having no control over the conditions of utilization of the product, we cannot assume any responsibility, legal or other, in regards of the results and/or any prejudice derived from.