

MARBLE & POLISHED STONE SEALER

www.saniten.ca

February 15, 2014

Solvent based impregnating sealer design not to enhance colors and protect natural stones leaving a natural look

DIRECTIONS

New installation: Surface must be clean, dry and free of all foreign matter. Apply only after the grout manufacture's recommended curing time. Minimum 7 days.

Resealing: Deep clean or remove any existing topical like sealer.

Application: Apply a generous coat of sealer evenly on the surface with SANITEN's White Nylon Scuff Pad TP-450 or a paint brush. Allow the sealer to sit on the surface for 15 to 20 minutes. Do not allow the sealer to dry during that time. Add more sealer or spread excess sealer on the surface if needed. Afterwards, remove excess sealer on the surface and let dry 30 minutes. Finally wipe off any apparent sealer on polished surfaces such as metal and glass insert with a soft dry cloth. Sealer will take 72 hours to gain full strength.

To verify if sealer protection is adequate: You can verify if the protection is adequate by putting a few drop of water on the sealed surface and wait a few minutes. If the surface doesn't darken, then protection is adequate. Otherwise add another coat of sealer.

CAUTION & LIMITATIONS

MAY IRRITATE EYES MAY IRRITATE SKIN
Do not get in eyes. Do not get on skin or clothing.
Do not breathe fumes. Keep out of reach of children. Keep away from flames or sparks.
FIRST AID TREATMENT
Contains mineral spirits. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes with eye lids open. If on skin, rinse thoroughly with water.

PACKAGING

500ml - 12 per case
946ml - 12 per case
4 litres - 4 per case
18.9 litres - pail

COVERAGE

946ml covers approximately 20m² (200ft²).

HANDLING & STORAGE

Avoid from freezing.
Store in original container, well closed in a dry area at room temperature.
Shelf life: 2 years
Do not put excess sealer in the garbage.
Dispose in an appropriate waste site.
Keep away from heat source, sparks and flames

TECHNICAL SUPPORT

Refer to the web site www.saniten.ca or call 1-877-726-5836.

Test first the product on a small and adequate area.

Protect the neighboring area against unexpected contact with the product. Product should be used at room temperature, between 10 and 25°C. Regular or sustained maintenance schedule may be required in heavily used and high traffic areas.

Product code: PS595

N.B. All information here above is accurate. But having no control over the conditions of utilization of the product, we cannot assume any responsibility, legal or other, in regards of the results and/or any prejudice derived from.

RECOMMENDED SURFACES:

- Marble & calcareous stones
- Natural stones (dense)
- All types of finishes, best on polished and honed surfaces
- Grout joints
- Floors, walls, counters & backsplashes
- Residential, commercial and institutional applications
- Interior & exterior use

CHARACTERISTICS:

CAUTION - IRRITANT

Solvent: OMS Odorless mineral spirit

- No color enhancement
- No sheen
- Doesn't form a superficial film when dry
- Protects against household dirt and stains
- Provides a water repellent and oil repellent protection

ENVIRONMENTAL DATA:

-VOC: 13gr/liter

REMOVER:

-Remover for Solvent based sealers PD1350

MAINTENANCE:

- Neutral Floor Cleaner N300
- Multi-Surface Cleaner BR110
- All Purpose Cleaner N313
- Glass & Stone Cleaner N323