

**PRODUCT:****PS675 NATURAL STONE SEALER – COLOR ENHANCER – SATIN GLOSS****DESCRIPTION**

Classification: floor sealer

WHMIS: D-2B Toxic product; B-3 Flammable product

Solvent based acrylic sealer formulated to protect and embellish natural stone surfaces.

**TECHNICAL DATA:**

Solvent base acrylic sealer

PH : 7.85

Color: clear

Leveling: good

Dries quickly

Enhances natural stones colors

Gloss rating: 15 - 20

Odor : aromatic

Cures to form a highly resistant barrier to staining from household water based and oil based contaminants

Flammability: yes; Flash point: &gt; 43°C

**ENVIRONMENTAL DATA:**

VOC: 85gr / 100ml

**APPLICATIONS:**

Protect against household dirt and stains

Provide a water repellent and oil repellent protection

Enhance colors with a satin finish

Type of surface: honed or textured

Surfacing: marbles and other calcareous stones, slate and other natural stones; including the cement grout joints

Floors, walls and counters\* (See Restrictions)

Residential, commercial and institutional use.

Interior application\*\*\*\* (See Restrictions)

**RESTRICTIONS:**

\*Sealer can be applied on kitchen counters but you must assure that the cleaning product used for maintenance will not damage the sealer as can do some dishwashing liquids or cleaners containing glycols or other chemical products that could be damageable.

\*\* Sealer should not be applied on surfaces with epoxy grout joints. For cement grout joints, you must also comply with the curing time required by the grout manufacturer before putting a sealer on the grout joints. Usually between 7 to 28 days.

\*\*\* The use of a sponge paint roller is not recommended because air bubbles are created and they could remain on the surface of the sealer after it has dried.

\*\*\*\* Sealer can be applied outside but surfaces cannot be grouted and outside temperature must remain between 10 and 30°C for 7 consecutive days and must be protected from rain during that period of time.

**SAFETY MEASURES DURING APPLICATION:**

Wearing of gloves, safety glasses and a breathing mask with organic vapors filter is recommended during applications.

**DIRECTIONS :**

**CAUTION:** It is required to test first the product on a small and adequate area to make sure that there are no incompatibilities between the product and the material on which the product is to be used on and therefore determine suitability and that result will meet consumer's expectations.

It is also required to always protect the neighboring area against unexpected contact with the product used (spills, splashes, etc) in order to prevent that surrounding material would be irreversibly altered and restored only by its replacement.

Product should be used at room temperature, between 10 and 25°C

**SHAKE WELL BEFORE USE**

**Surface preparation:**

**New installation:** Apply 1 coat of SANITEN Impregnator Sealer PS580 and 1 coat of Natural Stone Sealer / Color Enhancer before installing the tiles and grouting .and one coat of the Natural Stone Sealer / Color Enhancer sealer after grouting\*\* (See restrictions)

**Existing installation:** First deep clean surface or remove existing sealer with the appropriate SANITEN cleaner or remover. Follow directions in regards with the level of cleaning or removing required. Please note that a solvent based sealer cannot be applied over a water based sealer.

**Previously Sealed surfaces:** Deep clean the surfaces with the appropriate SANITEN cleaner and apply 1 thin coat of sealer. Usually 1 thin coat of sealer will be enough. It is not mandatory to remove existing sealer completely before applying a new coat of sealer unless the surface is much damaged or the existing sealer is water based.

**Sealer application:** Using a wax applicator, a paint roller for smooth or semi-smooth surfaces\*\*\* (See restrictions) or a solvent based paint brush, apply thin coats.

Allow to dry 4 to 6 hours between coats or until surface is totally dry.

Additional coats may be required depending on the porosity and the texture of the stone to seal.

Normal circulation after 24 hours.

Sealer gains full strength after 28 days

**Application on vertical surfaces:** make sure there is no accumulation of sealer in the top edges of the stones to avoid apparition of streaks from excess sealer during the drying period.

**MAINTENANCE:**

Use SANITEN Neutral Floor Cleaner N300

**COVERAGE:**

Varies with the porosity and the texture of the surface and the method of application

1 liter covers approximately 25m² (250ft²)

**REMOVER:**

Use SANITEN Solvent based Sealer Remover PD1350

**PACKAGING:**

| CODE     | FORMULA      | SIZE        | PACKING            |
|----------|--------------|-------------|--------------------|
| PS675-01 | Concentrated | 946ml       | Case of 12 bottles |
| PS675-04 | Concentrated | 4 liters    | Case of 4 bottles  |
| PS675-05 | Concentrated | 500ml       | Case of 12 bottles |
| PS675-20 | Concentrated | 18.9 liters | 1 pail             |

**CAUTION:**

Flammable product, contains MINERAL SPIRITS

Keep out of reach of children

MAY IRRITATE EYES Do not get in eyes. Do not swallow.

Wearing of gloves, safety glasses and a breathing mask with filters against organic vapors is recommended during interior applications

Before proceeding, test first on a small non visible area to assure safe use, suitability and results.

**HANDLING AND STORAGE:**

Avoid from freezing.

Keep away from heat, sparks and flames.

Store in original container, well closed in a dry area at room temperature.

Shelf life: 2 years

Do not put excess sealer in the garbage. Dispose in an appropriate waste site.

**TECHNICAL SUPPORT:**

Refer to the web site [www.saniten.ca](http://www.saniten.ca) or call 450-777-1536.

N.B. All information here above is accurate. But having no control over the conditions of utilization of the product, we cannot assume any responsibility, legal or other, in regards of the results and/or any prejudice derived from.

**Revision date:** February 26, 2011